



## SAFETY DATA SHEET

### CS-1800 Solvent Free Waterproofing Membrane

According to Appendix D, OSHA Hazard Communication Standard 29 CFR §1910.1200

#### 1. Identification

##### Product identifier

**Product name** CS-1800 Solvent Free Waterproofing Membrane

##### Recommended use of the chemical and restrictions on use

**Application** Moisture-Curing Waterproofing Coating.

**Uses advised against** No specific uses advised against are identified.

##### Details of the supplier of the safety data sheet

**Supplier** Concrete Sealants, Inc.  
9325 State Route 201,  
Tipp City,  
Ohio 45371  
US  
Tel.: 937-845-8776  
Fax: 937-845-3587  
Email: hello@conseal.com

##### Emergency telephone number

**Emergency telephone** Tel.: 937-845-8776 (6am to 5pm EST)  
Toll-free: 800-332-7325 (6am to 5pm EST)  
24-Hour Emergency Number: 1-800-424-9300 (CHEMTREC)

#### 2. Hazard(s) identification

##### Classification of the substance or mixture

**OSHA Regulatory Status** This Product is Hazardous under the OSHA Hazard Communication Standard.

**Physical hazards** Not Classified

**Health hazards** Skin Sens. 1 - H317 Repr. 1B - H360FD

**Environmental hazards** Aquatic Acute 3 - H402 Aquatic Chronic 3 - H412

**Human health** May cause skin sensitization or allergic reactions in sensitive individuals.

##### Label elements

##### Hazard symbols



**Signal word**

Danger

## CS-1800 Solvent Free Waterproofing Membrane

<b>Hazard statements</b>	H317 May cause an allergic skin reaction. H360FD May damage fertility. May damage the unborn child. H412 Harmful to aquatic life with long lasting effects.
<b>Precautionary statements</b>	P201 Obtain special instructions before use. P202 Do not handle until all safety precautions have been read and understood. P261 Avoid breathing vapor/ spray. P272 Contaminated work clothing must not be allowed out of the workplace. P273 Avoid release to the environment. P280 Wear protective gloves/ protective clothing/ eye protection/ face protection. P302+P352 If on skin: Wash with plenty of water. P308+P313 If exposed or concerned: Get medical advice/ attention. P333+P313 If skin irritation or rash occurs: Get medical advice/ attention. P362+P364 Take off contaminated clothing and wash it before reuse. P405 Store locked up. P501 Dispose of contents/ container in accordance with national regulations.
<b>Contains</b>	N-(3-(Trimethoxysilyl)propyl)ethylenediamine, Dibutyltin dilaurate, Bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate

### Other hazards

This product contains substances classified as PBT.

### 3. Composition/information on ingredients

#### Mixtures

<b>Limestone</b>	25 - <50%
CAS number: 1317-65-3	
Substance with National workplace exposure limits.	
<b>Trimethoxyvinylsilane</b>	1 - <2.5%
CAS number: 2768-02-7	
<b>N-(3-(Trimethoxysilyl)propyl)ethylenediamine</b>	0.25 - <0.5%
CAS number: 1760-24-3	
<b>Dibutyltin dilaurate</b>	0.025 - <0.25%
CAS number: 77-58-7	
<b>Bis(1,2,2,6,6-pentamethyl-4-piperidyl)sebacate</b>	0.025 - <0.25%
CAS number: 41556-26-7	
<b>Quartz (SiO<sub>2</sub>)</b>	0.025 - <0.25%
CAS number: 14808-60-7	

**Ingredient notes** The exact percentage/concentration is withheld as a trade secret in accordance with 29 CFR 1910.1200.

### 4. First-aid measures

#### Description of first aid measures

## CS-1800 Solvent Free Waterproofing Membrane

<b>General information</b>	Get medical attention immediately. Show this Safety Data Sheet to the medical personnel.
<b>Inhalation</b>	Remove affected person from source of contamination. Move affected person to fresh air and keep warm and at rest in a position comfortable for breathing. Maintain an open airway. Loosen tight clothing such as collar, tie or belt. When breathing is difficult, properly trained personnel may assist affected person by administering oxygen. Place unconscious person on their side in the recovery position and ensure breathing can take place.
<b>Ingestion</b>	Rinse mouth thoroughly with water. Move affected person to fresh air and keep warm and at rest in a position comfortable for breathing. Give a few small glasses of water or milk to drink. Stop if the affected person feels sick as vomiting may be dangerous. Do not induce vomiting unless under the direction of medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Never give anything by mouth to an unconscious person. Place unconscious person on their side in the recovery position and ensure breathing can take place.
<b>Skin Contact</b>	Remove contaminated clothing. Rinse with water. In the event of any sensitization symptoms developing, ensure further exposure is avoided.
<b>Eye contact</b>	Rinse immediately with plenty of water. Remove any contact lenses and open eyelids wide apart. Continue to rinse for at least 10 minutes.
<b>Protection of first aiders</b>	First aid personnel should wear appropriate protective equipment during any rescue.

### Most important symptoms and effects, both acute and delayed

<b>General information</b>	See Section 11 for additional information on health hazards. The severity of the symptoms described will vary dependent on the concentration and the length of exposure.
<b>Inhalation</b>	Prolonged inhalation of high concentrations may damage respiratory system.
<b>Ingestion</b>	Gastrointestinal symptoms, including upset stomach.
<b>Skin contact</b>	May cause skin sensitization or allergic reactions in sensitive individuals.
<b>Eye contact</b>	May cause temporary eye irritation.

### Indication of immediate medical attention and special treatment needed

<b>Notes for the doctor</b>	Treat symptomatically.
-----------------------------	------------------------

## 5. Fire-fighting measures

### Extinguishing media

<b>Suitable extinguishing media</b>	Extinguish with alcohol-resistant foam, carbon dioxide, dry powder or water fog. Use fire-extinguishing media suitable for the surrounding fire.
<b>Unsuitable extinguishing media</b>	Do not use water jet as an extinguisher, as this will spread the fire.

### Special hazards arising from the substance or mixture

<b>Specific hazards</b>	Containers can burst violently or explode when heated, due to excessive pressure build-up.
<b>Hazardous combustion products</b>	Thermal decomposition or combustion products may include the following substances: Harmful gases or vapors.

### Advice for firefighters

## CS-1800 Solvent Free Waterproofing Membrane

<b>Protective actions during firefighting</b>	Avoid breathing fire gases or vapors. Evacuate area. Cool containers exposed to heat with water spray and remove them from the fire area if it can be done without risk. Cool containers exposed to flames with water until well after the fire is out. If a leak or spill has not ignited, use water spray to disperse vapors and protect men stopping the leak. Avoid discharge to the aquatic environment. Control run-off water by containing and keeping it out of sewers and watercourses. If risk of water pollution occurs, notify appropriate authorities.
<b>Special protective equipment for firefighters</b>	Wear positive-pressure self-contained breathing apparatus (SCBA) and appropriate protective clothing. Standard Firefighter's clothing including helmets, protective boots and gloves will provide a basic level of protection for chemical incidents.

### 6. Accidental release measures

#### Personal precautions, protective equipment and emergency procedures

<b>Personal precautions</b>	Do not touch or walk into spilled material. Keep unnecessary and unprotected personnel away from the spillage. Wear protective clothing as described in Section 8 of this safety data sheet. Follow precautions for safe handling described in this safety data sheet. Ensure procedures and training for emergency decontamination and disposal are in place. Wash thoroughly after dealing with a spillage.
-----------------------------	---

#### Environmental precautions

<b>Environmental precautions</b>	Avoid discharge into drains or watercourses or onto the ground. Avoid discharge to the aquatic environment.
----------------------------------	---

#### Methods and material for containment and cleaning up

<b>Methods for cleaning up</b>	Wear protective clothing as described in Section 8 of this safety data sheet. Do not empty into drains. Absorb spillage with non-combustible, absorbent material. The contaminated absorbent may pose the same hazard as the spilled material. Collect and place in suitable waste disposal containers and seal securely. Label the containers containing waste and contaminated materials and remove from the area as soon as possible. Flush contaminated area with plenty of water. Wash thoroughly after dealing with a spillage. For waste disposal, see Section 13.
--------------------------------	---

<b>Reference to other sections</b>	For personal protection, see Section 8. See Section 11 for additional information on health hazards. See Section 12 for additional information on ecological hazards. For waste disposal, see Section 13.
------------------------------------	---

### 7. Handling and storage

#### Precautions for safe handling

<b>Usage precautions</b>	Read and follow manufacturer's recommendations. Keep away from food, drink and animal feeding stuffs. Wear protective clothing as described in Section 8 of this safety data sheet. Do not handle until all safety precautions have been read and understood. Handle all packages and containers carefully to minimize spills. Do not handle broken packages without protective equipment. Keep container tightly sealed when not in use. Avoid discharge to the aquatic environment.
<b>Advice on general occupational hygiene</b>	Wash promptly if skin becomes contaminated. Take off contaminated clothing and wash before reuse. Wash contaminated clothing before reuse. Do not eat, drink or smoke when using this product. Wash at the end of each work shift and before eating, smoking and using the toilet. Change work clothing daily before leaving workplace.

#### Conditions for safe storage, including any incompatibilities

## CS-1800 Solvent Free Waterproofing Membrane

<b>Storage precautions</b>	Store away from incompatible materials (see Section 10). Store in tightly-closed, original container in a dry, cool and well-ventilated place. Keep containers upright. Protect containers from damage. Utilize retaining walls to prevent soil and water pollution in the event of spillage. The storage area floor should be leak-tight, jointless and not absorbent.
<b>Storage class</b>	Miscellaneous hazardous material storage.
<b>Specific end uses(s)</b>	
<b>Specific end use(s)</b>	The identified uses for this product are detailed in Section 1.

### 8. Exposure controls/Personal protection

#### Control parameters

#### Occupational exposure limits

##### Limestone

Long-term exposure limit (8-hour TWA): OSHA 5 mg/m<sup>3</sup> respirable fraction

Long-term exposure limit (8-hour TWA): OSHA 5 mg/m<sup>3</sup> respirable fraction

Long-term exposure limit (8-hour TWA): OSHA 5 mg/m<sup>3</sup> respirable fraction

Long-term exposure limit (8-hour TWA): OSHA 15 mg/m<sup>3</sup> total dust

Long-term exposure limit (8-hour TWA): OSHA 15 mg/m<sup>3</sup> total dust

Long-term exposure limit (8-hour TWA): OSHA 15 mg/m<sup>3</sup> total dust

##### Quartz (SiO<sub>2</sub>)

Long-term exposure limit (8-hour TWA): OSHA 0.05 mg/m<sup>3</sup> respirable dust

Long-term exposure limit (8-hour TWA): ACGIH 0.025 mg/m<sup>3</sup> respirable fraction

A2

OSHA = Occupational Safety and Health Administration.

ACGIH = American Conference of Governmental Industrial Hygienists.

A2 = Suspected Human Carcinogen.

#### Amorphous silica (CAS: 67762-90-7)

**Immediate danger to life and health** 3000 mg/m<sup>3</sup>

#### Quartz (SiO<sub>2</sub>) (CAS: 14808-60-7)

**Immediate danger to life and health** 25 mg/m<sup>3</sup> 50 mg/m<sup>3</sup>

#### Exposure controls

##### Protective equipment



##### Appropriate engineering controls

Provide adequate ventilation. Personal, workplace environment or biological monitoring may be required to determine the effectiveness of the ventilation or other control measures and/or the necessity to use respiratory protective equipment. Use process enclosures, local exhaust ventilation or other engineering controls as the primary means to minimize worker exposure. Personal protective equipment should only be used if worker exposure cannot be controlled adequately by the engineering control measures. Ensure control measures are regularly inspected and maintained. Ensure operatives are trained to minimize exposure.

## CS-1800 Solvent Free Waterproofing Membrane

<b>Eye/face protection</b>	Eyewear complying with an approved standard should be worn if a risk assessment indicates eye contact is possible. Personal protective equipment for eye and face protection should comply with OSHA 1910.133. Unless the assessment indicates a higher degree of protection is required, the following protection should be worn: Tight-fitting safety glasses.
<b>Hand protection</b>	Chemical-resistant, impervious gloves complying with an approved standard should be worn if a risk assessment indicates skin contact is possible. The most suitable glove should be chosen in consultation with the glove supplier/manufacturer, who can provide information about the breakthrough time of the glove material. To protect hands from chemicals, gloves should comply with OSHA 1910.138 and be demonstrated to be impervious to the chemical and resist degradation. Considering the data specified by the glove manufacturer, check during use that the gloves are retaining their protective properties and change them as soon as any deterioration is detected. Frequent changes are recommended.
<b>Other skin and body protection</b>	Appropriate footwear and additional protective clothing complying with an approved standard should be worn if a risk assessment indicates skin contamination is possible.
<b>Hygiene measures</b>	Provide eyewash station and safety shower. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reuse. Clean equipment and the work area every day. Good personal hygiene procedures should be implemented. Wash at the end of each work shift and before eating, smoking and using the toilet. When using do not eat, drink or smoke. Preventive industrial medical examinations should be carried out. Warn cleaning personnel of any hazardous properties of the product.
<b>Respiratory protection</b>	Respiratory protection complying with an approved standard should be worn if a risk assessment indicates inhalation of contaminants is possible. Ensure all respiratory protective equipment is suitable for its intended use and is NIOSH approved. Check that the respirator fits tightly and the filter is changed regularly.
<b>Environmental exposure controls</b>	Keep container tightly sealed when not in use. Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

### 9. Physical and chemical properties

#### Information on basic physical and chemical properties

<b>Appearance</b>	Viscous liquid.
<b>Color</b>	Black.
<b>Odor</b>	Mild.
<b>Odor threshold</b>	Not available.
<b>pH</b>	Not available.
<b>Melting point</b>	Not available.
<b>Initial boiling point and range</b>	Not available.
<b>Flash point</b>	Not available.
<b>Evaporation rate</b>	Not available.
<b>Upper/lower flammability or explosive limits</b>	Not available.
<b>Vapor pressure</b>	Not available.
<b>Vapor density</b>	Not available.
<b>Relative density</b>	1.36-1.40

## CS-1800 Solvent Free Waterproofing Membrane

<b>Bulk density</b>	11.33-11.67 lb/Ga
<b>Solubility(ies)</b>	Not known.
<b>Partition coefficient</b>	Not available.
<b>Auto-ignition temperature</b>	Not available.
<b>Decomposition Temperature</b>	Not available.
<b>Viscosity</b>	35,000-70,000 cP @ 20°C
<b>Explosive properties</b>	Not considered to be explosive.
<b>Oxidizing properties</b>	Does not meet the criteria for classification as oxidizing.
<b>Other information</b>	No information required.

### 10. Stability and reactivity

<b>Reactivity</b>	See the other subsections of this section for further details.
<b>Stability</b>	Stable at normal ambient temperatures and when used as recommended. Stable under the prescribed storage conditions.
<b>Possibility of hazardous reactions</b>	This product hydrolyzes when it comes into contact with atmospheric moisture to form methanol.
<b>Conditions to avoid</b>	There are no known conditions that are likely to result in a hazardous situation.
<b>Materials to avoid</b>	No specific material or group of materials is likely to react with the product to produce a hazardous situation.
<b>Hazardous decomposition products</b>	Does not decompose when used and stored as recommended. Thermal decomposition or combustion products may include the following substances: Harmful gases or vapors.

### 11. Toxicological information

#### Information on toxicological effects

##### Acute toxicity - oral

**Notes (oral LD<sub>50</sub>)** Based on available data the classification criteria are not met.

##### Acute toxicity - dermal

**Notes (dermal LD<sub>50</sub>)** Based on available data the classification criteria are not met.

##### Acute toxicity - inhalation

**Notes (inhalation LC<sub>50</sub>)** Based on available data the classification criteria are not met.

**ATE inhalation (vapours mg/l)** 1,123.82

##### Skin corrosion/irritation

**Animal data** Based on available data the classification criteria are not met.

##### Serious eye damage/irritation

**Serious eye damage/irritation** Based on available data the classification criteria are not met.

##### Respiratory sensitization

**Respiratory sensitization** Based on available data the classification criteria are not met.

##### Skin sensitization

## CS-1800 Solvent Free Waterproofing Membrane

<b>Skin sensitization</b>	The product contains a sensitizing substance. May cause sensitisation by skin contact.
<b><u>Germ cell mutagenicity</u></b>	
<b>Genotoxicity - in vitro</b>	Based on available data the classification criteria are not met.
<b><u>Carcinogenicity</u></b>	
<b>Carcinogenicity</b>	Based on available data the classification criteria are not met.
<b>IARC carcinogenicity</b>	Contains a substance/a group of substances which may cause cancer. IARC Group 1 Carcinogenic to humans.
<b><u>Reproductive toxicity</u></b>	
<b>Reproductive toxicity - fertility</b>	Based on available data the classification criteria are not met.
<b>Reproductive toxicity - development</b>	Based on available data the classification criteria are not met.
<b><u>Specific target organ toxicity - single exposure</u></b>	
<b>STOT - single exposure</b>	Not classified as a specific target organ toxicant after a single exposure.
<b><u>Specific target organ toxicity - repeated exposure</u></b>	
<b>STOT - repeated exposure</b>	Not classified as a specific target organ toxicant after repeated exposure.
<b><u>Aspiration hazard</u></b>	
<b>Aspiration hazard</b>	Based on available data the classification criteria are not met.
<b>General information</b>	The severity of the symptoms described will vary dependent on the concentration and the length of exposure.
<b>Inhalation</b>	Prolonged inhalation of high concentrations may damage respiratory system.
<b>Ingestion</b>	Gastrointestinal symptoms, including upset stomach.
<b>Skin Contact</b>	May cause skin sensitization or allergic reactions in sensitive individuals.
<b>Eye contact</b>	May cause temporary eye irritation.
<b>Route of exposure</b>	Ingestion Inhalation Skin and/or eye contact
<b>Target Organs</b>	No specific target organs known.
<b>Medical considerations</b>	Allergies.

### 12. Ecological information

<b>Toxicity</b>	Aquatic Chronic 3 - H412 Harmful to aquatic life with long lasting effects.
<b><u>Persistence and degradability</u></b>	
<b>Persistence and degradability</b>	The degradability of the product is not known.
<b><u>Bioaccumulative potential</u></b>	
<b>Bio-Accumulative Potential</b>	No data available on bioaccumulation.
<b>Partition coefficient</b>	Not available.
<b><u>Mobility in soil</u></b>	
<b>Mobility</b>	No data available.
<b><u>Other adverse effects</u></b>	
<b>Other adverse effects</b>	None known.



## CS-1800 Solvent Free Waterproofing Membrane

### 13. Disposal considerations

#### Waste treatment methods

##### **General information**

The generation of waste should be minimized or avoided wherever possible. Reuse or recycle products wherever possible. This material and its container must be disposed of in a safe way. Disposal of this product, process solutions, residues and by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any local authority requirements. When handling waste, the safety precautions applying to handling of the product should be considered. Care should be taken when handling emptied containers that have not been thoroughly cleaned or rinsed out. Empty containers or liners may retain some product residues and hence be potentially hazardous.

##### **Disposal methods**

Do not empty into drains. Dispose of surplus products and those that cannot be recycled via a licensed waste disposal contractor. Waste, residues, empty containers, discarded work clothes and contaminated cleaning materials should be collected in designated containers, labeled with their contents. Waste packaging should be collected for reuse or recycling. Incineration or landfill should only be considered when recycling is not feasible.

### 14. Transport information

#### **General**

The product is not covered by international regulations on the transport of dangerous goods (IMDG, IATA, DOT).

#### UN Number

**UN No. (International)** Not applicable.

**UN No. (DOT)** Not applicable.

#### UN proper shipping name

**Proper shipping name (International)** Not applicable.

**Proper shipping name (DOT)** Not applicable.

#### Transport hazard class(es)

**Transport Labels (International)** No transport warning sign required.

#### **DOT transport labels**

No transport warning sign required.

#### Packing group

**Packing group (International)** Not applicable.

**DOT packing group** Not applicable.

#### Environmental hazards

##### **Environmentally Hazardous Substance**

No.

#### Special precautions for user

Not applicable.

**DOT reportable quantity** Not applicable.

**DOT TIH Zone** Not applicable.

## CS-1800 Solvent Free Waterproofing Membrane

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code Not applicable.

### 15. Regulatory information

#### US Federal Regulations

##### **SARA Section 302 Extremely Hazardous Substances Tier II Threshold Planning Quantities**

None of the ingredients are listed or exempt.

##### **CERCLA/Superfund, Hazardous Substances/Reportable Quantities (EPA)**

None of the ingredients are listed or exempt.

##### **SARA Extremely Hazardous Substances EPCRA Reportable Quantities**

None of the ingredients are listed or exempt.

##### **SARA 313 Emission Reporting**

The following ingredients are listed or exempt:

*Amorphous silica*

1.0 %

##### **CAA Accidental Release Prevention**

None of the ingredients are listed or exempt.

##### **FDA - Essential Chemical**

None of the ingredients are listed or exempt.

##### **FDA - Precursor Chemical**

None of the ingredients are listed or exempt.

##### **SARA (311/312) Hazard Categories**

None of the ingredients are listed or exempt.

##### **OSHA Highly Hazardous Chemicals**

None of the ingredients are listed or exempt.

#### US State Regulations

##### **California Proposition 65 Carcinogens and Reproductive Toxins**

None of the ingredients are required to be listed.

##### **California Air Toxics "Hot Spots" (A-I)**

None of the ingredients are listed or exempt.

##### **California Air Toxics "Hot Spots" (A-II)**

None of the ingredients are listed or exempt.

##### **California Directors List of Hazardous Substances**

The following ingredients are listed or exempt:

*Amorphous silica*

##### **Massachusetts "Right To Know" List**

The following ingredients are listed or exempt:

*Amorphous silica*

*Limestone*

*Quartz (SiO<sub>2</sub>)*

## CS-1800 Solvent Free Waterproofing Membrane

### Rhode Island "Right To Know" List

The following ingredients are listed or exempt:

*Limestone*

*Quartz (SiO<sub>2</sub>)*

### Minnesota "Right To Know" List

The following ingredients are listed or exempt:

*Amorphous silica*

*Limestone*

*Quartz (SiO<sub>2</sub>)*

### New Jersey "Right To Know" List

The following ingredients are listed or exempt:

*Limestone*

*Quartz (SiO<sub>2</sub>)*

### Pennsylvania "Right To Know" List

The following ingredients are listed or exempt:

*Amorphous silica*

*Limestone*

*Quartz (SiO<sub>2</sub>)*

### Inventories

#### US - TSCA

All the ingredients are listed or exempt.

#### US - TSCA 12(b) Export Notification

None of the ingredients are listed or exempt.

### 16. Other information

#### Abbreviations and acronyms used in the safety data sheet

TDG: The transport of dangerous goods act

IATA: International air transport association.

ICAO: Technical instructions for the safe transport of dangerous goods by air.

IMDG: International maritime dangerous goods.

CAS: Chemical abstracts service.

ATE: Acute toxicity estimate.

LC<sub>50</sub>: Lethal concentration to 50 % of a test population.

LD<sub>50</sub>: Lethal dose to 50% of a test population (median lethal dose).

EC<sub>50</sub>: 50% of maximal effective concentration.

PBT: Persistent, bioaccumulative and toxic substance.

vPvB: Very persistent and very bioaccumulative.

#### Classification abbreviations and acronyms

Aquatic Chronic = Hazardous to the aquatic environment (chronic)

#### Training advice

Read and follow manufacturer's recommendations. Only trained personnel should use this material.

#### Revision date

10/30/2019

## CS-1800 Solvent Free Waterproofing Membrane

<b>Revision</b>	1
<b>Supersedes date</b>	9/19/2018
<b>SDS No.</b>	8023
<b>Hazard statements in full</b>	H317 May cause an allergic skin reaction. H360FD May damage fertility. May damage the unborn child. H402 Harmful to aquatic life. H412 Harmful to aquatic life with long lasting effects.

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated. However, no warranty, guarantee or representation is made to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability of such information for his own particular use.